

Media Gateway™ Panel Module

S788



Standard Features

- Simple 'plug-in' connection to the L@titude Fire Alarm Control Panel
- Dual Line Dialer Capability (SIA or Contact ID)
- IP Capable (Sur-Gard Fibro)
- Programmable to report via point or zone
- Programmable for back-up reporting
- Reporting codes can be customized by user

Product Overview

The Media Gateway™ is a communication panel module for the L@titude Fire Alarm Control Panel.

The Media Gateway Panel Module provides connectivity to a remote monitoring center via Sur-Gard Fibro or dial-up. SIA is the recommended format for usage, but Contact ID is also supported. Transmission can be made through one or two telephone lines, and/or IP through Ethernet. Standard reporting codes have been pre-defined, although the user may customize these codes through the Loop Explorer 2 programming application.

The Media Gateway can provide connectivity to thirdparty networks (please consult a VES applications engineer for further information), and our new graphics system L@ti-View.

Technical Specifications	
Supply Voltage Range	24 VDC
Quiescent Current Consumption	114mA
Maximum Current Consumption	114mA
Dimensions	234.6mm x 62.8mm or 9.25" x 2.5"
Operating Temperature	23° F to 120° F (-5° C to 49° C)
Operating Humidity	to 95% (non condensing)

